



ICE 2 Door Freezer

TECHNICAL PERFORMANCE

LAYOUT

Two (2) Solid door Dynamic Freezer

BASE INSULATION

6 cm high density insulation across the bottom

INTERIOR

304 Stainless Steel interior

DOOR INSULATION

5 cm high density insulation

EXTERIOR

304 Stainless steel exterior except back, motor base and bottom

INSULATION DENSITY

PU CFC Free injected @ 40 kg/m²

SHELVES

Four (4) adjustable heavy duty Stainless steel wire shelves

CHASE TYPE

"Stainless Steel chase on 3" Castors (Optional 2" Castors or adjustable legs)"

DOORS

Heavy duty self close hinged doors

CONTROL

Digital Electronic Thermostat

GLASS DOORS

"Optional Stainless Steel Door frame with double glass vacuumed and insulated"

CONTROL PROTECTION

PVC protective cover for thermostat and switches

DOOR HANDLE

Built-in Stainless steel handles

CLIMATE CLASS

ST

DOOR GASKETS

Rubber gaskets with magnets

AMBIENT TEMPERATURE

32°C at RH 60%

LIGHTING

LED Inner lighting triggers when the door opens

REFRIGERANT

Gas R404A

REFRIGERATION TYPE

Manual Defrost

MOTOR PLACEMENT

Top Motor

BODY INSULATION

5 cm high density insulation across the back, top and sides

TEMPERATURE RANGE

Reach up to -20° C

DRAIN

Requires drain

POWER RATING

220-240 V, 1 PH, 50 HZ, 1kw



DIMENSIONS

- Length: 140 cm

- Width: 80 cm

- Height: 210 cm