



# UT (1) Door Refrigerator

## TECHNICAL PERFORMANCE

### LAYOUT

One(1) Door undercounter refrigerated storage

### BASE INSULATION

6 cm high density insulation across the bottom

### INTERIOR

304 Stainless Steel interior

### DOOR INSULATION

5 cm high density insulation

### EXTERIOR

304 Stainless steel exterior except back, motor base and bottom

### INSULATION DENSITY

PU CFC Free injected @ 40 kg/m2

### SHELVES

One (1) adjustable heavy duty white / grey galvanized wire shelf

### CHASE TYPE

"Stainless Steel chase on 3" Castors  
(Optional 2" Castors or adjustable legs)"

### DOORS

Heavy duty self close hinged doors

### CONTROL

Digital Electronic Thermostat

### GLASS DOORS

"Optional Stainless Steel Door frame with double glass vacuumed and insulated"

### CONTROL PROTECTION

PVC protective cover for thermostat and switches

### DOOR HANDLE

Built-in Stainless steel handles

### CLIMATE CLASS

ST

### DOOR GASKETS

Rubber gaskets with magnets

### AMBIENT TEMPERATURE

32°C at RH 60%

### LIGHTING

LED Inner lighting triggers when the door opens

### REFRIGERANT

Gas R134A

### REFRIGERATION TYPE

Low noise with dynamic airflow

### MOTOR PLACEMENT

Back motor to maximize frontal usage

### BODY INSULATION

5 cm high density insulation across the back, top and sides

### TEMPERATURE RANGE

"0°C to 8°C,

### DRAIN

Requires drain

### POWER RATING

220-240 V, 1 PH, 50 HZ, 0.3kw



### DIMENSIONS

- Length: 120 cm

- Width: 76 cm

- Height: 90 cm  
(Optional Height: 85 cm)